




Home Innovation
NGBS GREEN CERTIFIED™

THIS SIGNIFIES THE FOLLOWING CONSTRUCTION PRODUCTS

STEGO FOUNDATION VAPOR RETARDERS: STEGO WRAP,
STEGOHOME, STEGOCRAWL WRAP, AND DRAGO WRAP

MANUFACTURED BY
STEGO INDUSTRIES, LLC

ARE CERTIFIED FOR POINTS TOWARD NGBS GREEN CERTIFICATION TO THE ICC 700
NATIONAL GREEN BUILDING STANDARD, AS DETAILED BELOW.


Michael Luzier – President & CEO

05-15-2024
Approval Date

04-30-2026
Expiration Date

CERTIFICATE # 330

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer.



NGBS Green Certificate #NGBSGCP-000330

Product: Stego Foundation Vapor Retarders: Stego Wrap, StegoHome, StegoCrawl Wrap, and Drago Wrap

Manufacturer: Stego Industries, LLC

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

2020 NATIONAL GREEN BUILDING STANDARD			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONAL OF USE TO AWARD POINTS
602.1.1.1	A capillary break and vapor retarder are installed at concrete slabs. Mandatory.	Mandatory	Product is installed in accordance with IRC Sections R506.2.2 and R506.2.3 or IBC Sections 1907 and 1805.4.1.
602.1.4.1(1)	Min 6-mil vapor retarder is installed on the crawlspace floor that extends at least 6" up the wall and is attached and sealed to the wall. 6 points available.	6	Product is installed on the crawlspace floor of unconditioned vented crawl as directed.
602.1.4.2(1)	When crawlspace is built as conditioned space, crawlspace is sealed using a concrete slab over 6-mil polyethylene sheeting or other Class I vapor retarder. 8 points available.	8	Product is installed on the crawlspace walls of unconditioned vented crawl as directed.
602.1.4.2(2)	When crawlspace is built as conditioned area, crawlspace is sealed using 6-mil polyethylene sheeting, or other Class I vapor retarder. Mandatory.	Mandatory	Product is installed in accordance with Section 408.3 or Section 506 of the IRC.

2020 NATIONAL GREEN BUILDING STANDARD			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONAL OF USE TO AWARD POINTS
902.3.1.1	There is a continuous gas-permeable base course under each soil-gas retarder that is separated by foundation walls or footings. The soil-gas retarder is a continuous 6-mil (0.15 mm) polyethylene or equivalent. Compliance option for 902.3(1) and 902.3(2).	Mandatory	Items 902.3.1.2 through 902.3.1.7 are also met. Mandatory for buildings in Zone 1. For Zone 2 or 3 buildings, 6 points if a passive radon system is installed OR 12 points if an active radon system is installed.
501.1(2)(c)	An EPA-recognized brownfield lot is selected.	15	None.