



Home Innovation
NGBS GREEN CERTIFIED™

THIS SIGNIFIES THE FOLLOWING CONSTRUCTION PRODUCTS

CEMBOARD® SIDING PRODUCTS - CEMPLANK® AND CEMPANEL®;
PREVAIL® SIDING PRODUCTS, CEMTRIM® AND PREVAIL® SIDING

MANUFACTURED BY

JAMES HARDIE BUILDING PRODUCTS, INC.

ARE CERTIFIED FOR POINTS TOWARD NGBS GREEN CERTIFICATION TO THE ICC 700
NATIONAL GREEN BUILDING STANDARD, AS DETAILED BELOW.


Michael Luzier – President & CEO

09-30-2011
Approval Date

05-31-2026
Expiration Date

CERTIFICATE # 205

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer.



NGBS Green Certificate #NGBSGCP-000205

Product: Cemboard® Siding Products - Cemplank® and Cempanel®; Prevail® Siding Products, Cemtrim® and Prevail® Siding

Manufacturer: James Hardie Building Products, Inc.

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

2020 NATIONAL GREEN BUILDING STANDARD			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONAL OF USE TO AWARD POINTS
602.1.6	Termite-resistant materials are used for the foundation, all structural walls, floors, concealed roof spaces not accessible for inspection, exterior decks, and exterior claddings within the first 2 ft above the top of the foundation. 2 points available.	2-6	To earn two points, product is used in conjunction with other termite-resistant materials for the first 2 feet of all the foundation, floor, and structural wall, wall cladding, and exterior deck components in zones with slight to moderate termite infestation. Four points are awarded when used in conjunction with other termite-resistant materials for the first 3 feet in moderate to heavy termite zones, and six points are awarded for use with other termite-resistant materials for all of the foundation, floor, and structural wall, wall cladding, and exterior deck components in areas of very heavy termites.