Certificate #220

Home Innovation
NGBS GREEN CERTIFIED™

VIANCE PRESERVE (CA) PRESSURE TREATED LUMBER

MANUFACTURED BY:

VIANCE LLC

These products are certified for points toward NGBS Green Certification to the ICC 700 National Green Building Standard, as detailed below.

Michael Luzier, President, Home Innovation Research Labs	03-01-2013	12-31-2026
	Certification Date	Expiration Date

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance.
For details of the product warranty, consult the product manufacturer.

Home Innovation Research Labs | 400 Prince George's Boulevard | Upper Marlboro, MD 20774

Product: Viance Preserve (CA) Pressure Treated Lumber

Manufacturer: Viance LLC

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward product certification under the ICC 700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is (are) used as noted below.

2020 National Green Building Standard

Practice #	Description	Potential Points	Additional Conditions	Additional Certifications
503.2(4)	Erosion reduced through use of terracing, retaining walls, landscaping and restabilization.	6	Retaining walls built with this product must be an integral part of the installed landscape plan designed to limit long-term erosion.	
602.1.6	Termite-resistant materials are used for the foundation, all structural walls, floors, concealed roof spaces not accessible for inspection, exterior decks, and exterior claddings within the first 2 ft above the top of the foundation. 2 points available.	2-6	To earn 2 points, product is used in conjunction with other termite-resistant materials for the first 2′ of all the foundation, floor, and structural wall, wall cladding, and exterior deck components in zones with slight to moderate termite infestation. Four points are awarded when used in the first 3′ in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall cladding, and exterior deck components in areas of very heavy termites.	