



Home Innovation
NGBS GREEN CERTIFIED™


THIS SIGNIFIES THE FOLLOWING CONSTRUCTION PRODUCTS

VIANCE PRESERVE (CA) PRESSURE TREATED LUMBER

MANUFACTURED BY

VIANCE LLC

ARE CERTIFIED FOR POINTS TOWARD NGBS GREEN CERTIFICATION TO THE ICC 700
NATIONAL GREEN BUILDING STANDARD, AS DETAILED BELOW.


Michael Luzier – President & CEO

03-01-2013
Approval Date

12-31-2026
Expiration Date

CERTIFICATE # 220

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer.



NGBS Green Certificate #NGBSGCP-000220

Product: Viance Preserve (CA) Pressure Treated Lumber

Manufacturer: Viance LLC

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

2020 NATIONAL GREEN BUILDING STANDARD			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONAL OF USE TO AWARD POINTS
503.2(4)	Erosion reduced through use of terracing, retaining walls, landscaping and restabilization.	6	Retaining walls built with this product must be an integral part of the installed landscape plan designed to limit long-term erosion.
602.1.6	Termite-resistant materials are used for the foundation, all structural walls, floors, concealed roof spaces not accessible for inspection, exterior decks, and exterior claddings within the first 2 ft above the top of the foundation. 2 points available.	2-6	To earn 2 points, product is used in conjunction with other termite-resistant materials for the first 2' of all the foundation, floor, and structural wall, wall cladding, and exterior deck components in zones with slight to moderate termite infestation. Four points are awarded when used in the first 3' in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall cladding, and exterior deck components in areas of very heavy termites.